


8 | 7 | 6 | 5 | 4 | 3 | 2 | 1

THIS DOCUMENT IS THE PROPERTY OF DME INC., AND CANNOT BE
DISTRIBUTED WITHOUT DME'S AUTHORIZATION

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED

BILL OF MATERIAL

ITEM	QTY	DESCRIPTION	MATERIAL
1	2	MALE NPT SCH. 40 STEEL	A 53-E GR.B
2	4	BRAID COLLAR	A 240 T-304
3	2	STD. WT. L.R. 45° WELD ELBOW	A 234 GR.WPB
4A	2	METAL CONVOLUTED HOSE	A 240 T-321
4B	2	METAL BRAID	A 240 T-304
5	1	STD. WT. L.R. 90° WELD ELBOW	A 234 GR.WPB



SIZE	A	B	ASSEMBLY PART NUMBER
1/2"	17.88"	29.54"	DM8222-0050-3
3/4"	19.19"	32.26"	DM8222-0075-3
1"	20.88"	35.29"	DM8222-0100-3
1-1/4"	22.37"	37.63"	DM8222-0125-3
1-1/2"	23.88"	40.03"	DM8222-0150-3
2"	25.88"	44.36"	DM8222-0200-3
2-1/2"	28.75"	50.16"	DM8222-0250-3

ALL DIMENSIONS ARE IN INCHES



DME INC.

14001 MARQUARDT AVE.
SANTA FE SPRINGS, CA
90670
TEL: 562-921-0464
FAX: 562-802-7489

ANY CHANGES ON THE
DRAWING MUST BE
REPORTED AND APPROVED
ONLY BY
THE ENGINEERING DEPARTMENT

CUST:
JOB#

DESIGN: PER CUST. II-12-03

SIZE -

DWG NO. DM8222-3 REV.

APPROVED BY: E.F. II-12-03

SCALE

DATE: II-12-03 SHT

DWG: M.N. II-12-03

NONE

1 OF 1

SEISMIC CONNECTOR W/ MALE NPT

UNLESS OTHERWISE SPECIFIED
TOLERANCES ARE :

FRACTIONS:
.XXX ± .010"
.XX ± .030"
± 1/8"

EXP. JOINTS:
.X ± .060"
ANGLES ± 1/2°
OAL: ± 1/8"