	8 7	6	5	<i>ــــــــــــــــــــــــــــــــــــ</i>		3	2	
	THIS DOCUMENT IS THE PROPERTY OF DME INC., AND CANNOT BE DISTRIBUTED WITHOUT DME'S AUTHORIZATION		REVISIONS	DATE APPROVED	BILL OF MATERIAL			
D					ITEM QT 1 2 2 4 3 4 4 2 5A 2 5B 1	BRAID COLLAR + STD. WT. L.R. 90° WE METAL CONVOLUTED	ELD ELBOW HOSE	MATERIAL A 53-E GR.B A 240 T-304 A234 GR.WPE A 240 T-321 A 240 T-304 A 53-E GR.B
		Z Z				LIFTING LUG, (PROVIE OPTIONAL DRAIN PLU	ED ON 4" THRU 12")	C/S C/S
С						GENERAL NOT	FS.	
						A. ALL WELDI WITH ASME B. PRESSURE	NG T.I.G. (HELI-A SECTION IX.	RC) IN ACCORDANCE BLIES AIR UNDER , NO LEAKAGE.
В	B <u>SEISMIC CC</u> FOR ± <u>3" EACH LEG</u> OF M		SIZE A 1-2" 17.75' 3/4" 19.50' 1" 21.25'	B NI 10.00" DM824 13.50" DM824	SEMBLY PART JMBER +3-0050-3 +3-0075-3 43-0100-3	EXPANSION BE INSPECT NECESSAR)	FED FOR DAMAGE	X CONNECTORS MUST AND REPLACED IF
	ALL DIMENSIONS ARE IN INCHES		I-I/4" 23.00 I-I/2" 24.75 2" 27.50 2-I/2" 30.75	" 17.00" DM824			PO#:	
А	DME INC. ILOOI MARQUARDT SANTA FE SPRING 90670 TEL: 562-92I-04.64 FAX: 562-802-74.87	AVE. DRAWING MUST BE REPORTED AND APPROV ONLY BY 4 THE ENGINEERING DEPART	E JOB# DESIGN: PER CUS MENT APPROVED BY: E	01 00 E010	ZE _ CALE	I80° SEISMIC C W/ MALE PIPE DWG NO. DM8243 DATE: 01-30-2013	THREADS	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE : .XXX ± .010" .XX ± .030" .X ± .060" ANGLES ± 1/2° 0AL: ± 1/8"
	8 7 1	6	5 🕇	4		3	2	

C:\Users\CAD\Desktop\New Folder\DM8243-3.dwg, 5/21/2013 10:40:05 AM, by: M.N,

by: M.N